

TECHNICAL DATA - HOLDON® BANNAEDGE BANNER EDGE REINFORCEMENT TAPE

DESCRIPTION

A laminated construction using a siliconised HDPE and high tack acrylic adhesive to produce a self wound liner free tape. The tape itself will withstand external use and can have a life expectancy in excess of 2 years if correctly used and applied. Fade or discoloration will depend on exposure to and intensity of UV and weather conditions.

TECHNICAL DATA - FOIL

Materials	200 micron High Density PE foil		
Weight	196 gsm		
Tensile Strength	MD 4.0 kN/M	ASTM D862	
	TD 4.4 kN/M	ASTM D862	
Elongation	MD 1400 %	ASTM D862	
	TD 1800%	ASTM D862	
Opacity	85%	ISO 2471	

ADHESIVE CONTENT - HIGH TACK MODIFIED ACRYLIC

Coating Weight	100 gsm
Adhesive thickness	100 micron
Adhesive strength (24 hour 300mm/min peel)	25N / 25mm
Adhesive temp performance	-40C +160 C°
Colours	White
Roll Size	40 mm width
Roll length	25 m



NOTE

All technical data is based on average values. Statements, technical information and recommendations contained herein are based on tests we believe to be reliable.

The user shall determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection herewith.

RECYCLABILITY

If fixed onto a polythene, banner/substrate, they can be recycled together, subject to proper collection and sorting according to purity.

08.01.2011